

## Lightest, thinnest, rugged laptop in the world

AMREL leveraged its 20 years of experience to produce a fully rugged laptop that's just an inch thick and so light that you can hold it in one hand. You no longer have to choose between genuine toughness and a convenient, portable form factor.

## Rugged

When you're in the field, you can have confidence in the ROCKY RS11. Certified to MIL-STD 810 and with standard Solid State Hard Drive, the ROCKY RS11 can survive the harshest environments.

#### **Powerful**

High-performance doesn't just live in the office. Wherever you are, whatever you're doing, the ROCKY RS11's powerful i7 processor can handle the demands of the most resource-demanding applications.

#### **Applications**

Perfect for applications that require rigorous field work, heavy data input, and a large display, the ROCKY RS11can be used for:

- Onsite Data Collection & Management
- Front-Line Mapping & Situational Awareness
- Oil & Gas, Mining, & Construction
- Field Research & Surveying
- Combat Control Solutions



# RS11 Technical Specifications

10 10 10 10 10 10 10 10 10 10 10 10 10 1		
Item	Standard	Upgrades
<b>Environmental Rating</b>	MIL-STD 810G & IP-65 Certified	MIL-STD 461F (Military Package only)
Operating System	Windows® 7or 8	
CPU	Intel® Core™ i71.7 GHz Processor (Turbo Boost: Up to 2.8 GHz	<u>z</u> ),
	4MB Intel® Smart Cache	
Memory	4GB DDR3 1600 MHz	Max: 8GB DDR3 1600 MHz
Graphics	Intel® HD Graphics 4000	
Display	13.3" HD+ (1600 x900) LCD with LED B/L	Night Vision
	(IPS), Sunlight Readable	
Storage	Removable 2.5" 120GB SATA II/III Solid State Hard Drive	Upgradeable to 480GB
Audio	HD Audio and Stereo Speakers, Embedded Digital Mic	
Keyboard	87-key with Backlight (Membrane Type)	
Touchpad	Capacitive Touchpad with Multi-touch	
	(Win 8 compatible)	
I/O Interface	Left:	
	SD Card Slot x 1, SIM Card Slot x 1, USB 3.0 x 1,	
	USB 3.0 x 1 with fast charger, GLAN RJ45	
	Rear:	Sealed Fisher Connectors 1~5 (USB 2.0, VGA,
	DC-in Connector x 1	RS232/RS422, GLAN, Audio)
	Bottom:	
	Multi Bay port x 1 (PCI-e x 1, USB 3.0 x 1,	
	USB 2.0 x 1, Power - VBATA/1A & 5V/1A	
B	(reserved for future use)	
Power	Main Battery:	
	Removable Battery Pack:	
	Li-ion Polymer 11.1V/6040mAh battery	
	<b>AC Adapter:</b> 90W AC 100V~240V 50/60Hz	
	DC In:	Military 3pin twisted lock
	19V	Willitary Spirit Wisted lock
	134	
Color	Black or NATO Green	
Overall Dimensions	13.3 in x 10.4 in x 1.1 in	
C.C. GIII DIIII CII SIOII S	338mm(L) x 265mm (W) x 28mm (H) (with bumper guards)	
Weight	5.5 lbs (2.5 Kg) (with battery)	
	( ( :-g) ( &date.))	
Integrated Options	Optional	Standard Environmental Ratings
Wireless I AN/PAN	Intel® Centrino Advanced-N 6235	MIL CTD 010C Contifeed

Integrated Options	Optional
Wireless LAN/PAN	Intel® Centrino Advanced-N 6235
	(802.11 a/b/g/n) /Bluetooth®
Wireless WAN	Gobi 3000 HSDPA (AirPrime MC8305)
GPS	Ublox LEA-6H
Security	TPM v1.2 module
Vehicle Adapter	DC-in 12V-32V (with or without surge protector)

\* Contact us for more information
\* \* Specifications subject to change

Specifications subject to change without notice

#### MIL-STD 810G Certified

Rain

Shock 516.6, Procedure I

Vibration A. 514.6, Procedure 1, Category 20

B. 514.6, Procedure I, Category 14

C. 514.6, Procedure I, Category 1

506.5, Procedure II

Humidity 507.5

Salt Fog 509.5

Altitude Method 500.5, Procedure I, II

Operating: 15,000 ft (4,572 m) Storage: 40,000 ft (12,180 m)

Method 501.5, Procedure I and II High/Low Temperature

Method 502.5, Procedure I and II Operating:  $-4^{\circ}F$  to  $131^{\circ}F$  /  $-20^{\circ}C$  to  $55^{\circ}C$ Storage: -40°F to 158°F / -40°C to 70°C (Optional Upgrade: Operating: -22°F to

131°F / -30°C to 55°C)

**Temperature Shock** Method 503.5, Procedure I-A

Operating: -4°F to 140°F/-20°C to 60°C

**IEC IP-65 Certified** Dust-protected; water jet



























120 Iber Road Suite 103, Ottawa, Ontario, K2S 1E9 Office +1 (613) 686-7006 | Fax +1 (613) 836-3758 info@laurentiantech.ca | www.laurentiantech.ca



